



NOTE 1:
 JOBSITE VOLTAGE MUST BE KNOWN TO IDENTIFY ELECT. WIRE SELECTION PER THE FOLLOWING:
 1 20KV/200V, 245KV/230V
 2 3.0KV/200V, 37KV/230V
 3 3.3KV/265V
 4 3.7KV/200V, 4.5KV/230V
 5 4.0KV/200V, 4.0KV/265V
 6 1.6KV/200V, 2.0KV/230V,
 2.7KV/265V
 7 2.5KV/200V, 3.0KV/230V,
 4.0KV/265V
 8 2.5KV/200V, 3.5KV/230V
 9 3.7KV/200V

NOTE 2:
 FOR USE ON 200V/300 200V/230V ELECT. W/ CHASSIS W/ POWER DELIVER BY OTHER, ANY OTHER USAGE IS NON-UL

NOTE 3:
 20A LINE CORD WILL BE USED WITH A. I.C.A. CO. 20A CIRCUIT BREAKER. POWER CONNECTION

- (SEE NOTE 1)
- G-NO HEAT
 - 1-25KW ELECTRIC
 - 2-30KW "
 - 3-33KW "
 - 4-37KW "
 - 5-40KW "
 - 6-46KW "
 - 7-25KW "
 - 8-29KW "
 - 9-32KW "
 - H-HOT WATER
 - S-STEAM
 - X-SPECIAL

- ** T04 STYLE HTR
- * NON-UL
- * NOT AVAILABLE ON-OS-OR
- * LUMP-LIMITED RANGE HEAT PUMP

II	REVISION	NO. TO PAGE	TO	DATE	BY	REV
1	1	1	1	11/05	11/05	1
2	2	2	2	11/05	11/05	2
3	3	3	3	11/05	11/05	3
4	4	4	4	11/05	11/05	4

684799

703 PRODUCT CODING CHASSIS

684799