



TRANQUILITY® 16 SERIES



# THE TRANQUILITY® 16 COMPACT (TC) SERIES



The Tranquility® 16 Compact (TC) Series raises the bar for water-source heat pump efficiencies, features and application flexibility. Not only does the Tranquility 16 Compact Series exceed ASHRAE 90.1 efficiencies, but it also uses EarthPure® (HFC-410A) zero ozone depletion refrigerant, making it an extremely environmentally-friendly option.

With one of the smallest cabinets in the industry, the Tranquility® 16 Compact (TC) Series will easily fit into tight spaces. Designed to be backward compatible with thousands of older water-source heat pumps, the Tranquility® 16 Compact (TC) Series heat pump is packed full of the innovation you have come to expect from the experts at ClimateMaster.

## UNIT FEATURES

- Sizes 006 (1/2 ton, 1.8 kW) through 060 (5 tons, 17.6 kW)
- EarthPure® (HFC-410A) refrigerant
- Exceeds ASHRAE 90.1 efficiencies
- Galvanized steel construction with attractive matte black epoxy powder coat paint front access panel
- Epoxy powder painted galvanized steel drain pan
- Sound absorbing glass fiber insulation
- Unique double isolation compressor mounting for quiet operation
- Insulated divider and separate compressor/air handler compartments
- Copeland scroll compressors (size 024 and above)
- TXV metering device
- Microprocessor controls standard (optional DXM and/or DDC controls)
- Field convertible discharge air arrangement for horizontal units

Easy to remove blower housing for quick service and PSC three-speed fan motor

Easy service access from multiple sides



Dual compressor vibration isolation for quiet operation



Easy access control box contains advanced digital controls with Remote Service Sentinel Optional Enhanced controls (DXM) & DDC Controllers



Factory installed hanger brackets on horizontal units



Epoxy powder painted drain pan with condensate overflow protection



## PERFORMANCE AND SPECIFICATIONS

### AHRI/ISO/ASHRAE 13256-1 Data (English (I-P) Units & Metric (S-I) Units)

Model	Refrigerant	Water Loop Heat Pump				Ground Water Heat Pump				Ground Loop Heat Pump			
		Cooling 86°F [30°C]		Heating 68°F [20°C]		Cooling 59°F [15°C]		Heating 50°F [10°C]		Cooling 77°F [25°C]		Heating 32°F [0°C]	
		Capacity	EER	Capacity	COP	Capacity	EER	Capacity	COP	Capacity	EER	Capacity	COP
		Btuh [kW]	Btuh/W [W/W]	Btuh [kW]		Btuh [kW]	Btuh/W [W/W]	Btuh [kW]		Btuh [kW]	Btuh [kW]	Btuh/W [W/W]	
TC-006	HFC-410A	5,800 [1.70]	13.2 [3.9]	7,500 [2.20]	4.7	6,900 [2.02]	21.1 [6.2]	6,200 [1.82]	4.0	6,200 [1.82]	15.4 [4.5]	4,900 [1.44]	3.4
TC-009	HFC-410A	8,800 [2.58]	13.4 [3.9]	11,600 [3.40]	4.2	10,100 [2.96]	21.0 [6.2]	9,800 [2.87]	3.9	9,300 [2.72]	15.7 [4.6]	7,900 [2.31]	3.4
TC-012	HFC-410A	11,700 [3.43]	13.5 [4.0]	15,200 [4.45]	4.3	13,700 [4.01]	20.8 [6.1]	12,500 [3.66]	3.8	12,000 [3.52]	14.9 [4.4]	9,900 [2.90]	3.2
TC-015	HFC-410A	14,500 [4.25]	15.4 [4.5]	17,300 [5.07]	5.0	16,800 [4.92]	24.5 [7.2]	14,400 [4.22]	4.4	15,000 [4.39]	17.2 [5.0]	11,100 [3.25]	3.6
TC-018	HFC-410A	17,300 [5.07]	14.3 [4.2]	21,500 [6.30]	5.0	20,600 [6.04]	24.2 [7.1]	17,200 [5.04]	4.4	18,400 [5.39]	16.3 [4.8]	13,900 [4.07]	3.4
TC-024	HFC-410A	23,700 [6.94]	13.4 [3.9]	28,500 [8.35]	4.7	26,700 [7.82]	20.9 [6.1]	24,000 [7.03]	4.1	24,900 [7.30]	15.4 [4.5]	18,500 [5.42]	3.3
TC-030	HFC-410A	28,100 [8.23]	13.4 [3.9]	35,100 [10.28]	4.6	31,700 [9.29]	20.1 [5.9]	29,600 [8.67]	4.1	28,900 [8.47]	15.1 [4.4]	23,400 [6.86]	3.4
TC-036	HFC-410A	34,500 [10.11]	13.5 [4.0]	45,200 [13.24]	4.4	38,700 [11.34]	20.7 [6.1]	37,500 [10.99]	4.0	35,300 [10.34]	14.9 [4.4]	29,600 [8.67]	3.3
TCV041	HFC-410A	37,000 [10.84]	13.2 [3.9]	46,000 [13.48]	4.2	41,800 [12.25]	19.4 [5.68]	38,700 [11.34]	3.8	38,000 [11.13]	14.5 [4.2]	30,700 [9.00]	3.1
TC-042	HFC-410A	40,100 [11.75]	13.1 [3.8]	52,700 [15.44]	4.3	45,900 [13.45]	19.6 [5.7]	44,000 [12.89]	3.8	40,500 [11.87]	14.4 [4.2]	34,300 [10.05]	3.2
TC-048	HFC-410A	47,700 [13.98]	13.3 [3.9]	55,900 [16.38]	4.7	54,300 [15.91]	20.5 [6.0]	46,500 [13.62]	4.1	49,000 [14.36]	14.7 [4.3]	36,400 [10.67]	3.4
TC-060	HFC-410A	59,400 [17.40]	13.4 [3.9]	77,000 [22.58]	4.3	66,600 [19.51]	19.9 [5.8]	64,000 [18.75]	3.8	60,100 [17.61]	14.8 [4.3]	50,500 [14.80]	3.1

Cooling capacities based upon 80.6°F [27°C] DB, 66.2°F [19°C] WB entering air temperature.

Heating capacities based upon 68°F [20°C] DB, 59°F [15°C] WB entering air temperature.

All ratings based upon operation at the lower voltage of dual voltage rated models.

### Dimensional Data

Vertical Upflow Model		Overall Cabinet			Horizontal Model		Overall Cabinet		
		W	D	H			W	D	H
006 - 012	in. cm	19.1	19.1	22.0	006 - 012	in. cm	19.1	34.1	11.1
		48.5	48.5	55.9			48.5	86.6	28.2
015 - 018	in. cm	21.5	21.5	39.0	015 - 018	in. cm	20.1	43.1	17.0
		54.6	54.6	99.1			51.1	109.5	43.2
024 - 030, 041	in. cm	21.5	21.5	40.0	024 - 030	in. cm	20.1	43.1	18.3
		54.6	54.6	101.6			51.1	109.5	46.5
036 - 042	in. cm	21.5	26.0	45.0	036 - 042	in. cm	20.1	47.1	21.0
		54.6	66.0	114.3			51.1	119.6	53.3
048 - 060	in. cm	24.0	32.5	46.0	048 - 060	in. cm	24.1	54.1	21.0
		61.0	82.6	116.8			61.2	137.4	53.3

### Voltage Options

Model	Volts	Hz	Phase
006 - 024	208/230	60	1
	265		
030 - 036	208/230	60	1
	265	60	3
	208/230	60	3
	460	60	3
041 - 060	208/230	60	1
	208/230	60	3
	460	60	3
	575	60	3

