

TRANQUILITY CASED COIL (TAC)



The Tranquility Cased Coil has the highest efficiency ratings of any geothermal split system in the industry when matched with ClimateMaster Tranquility indoor or outdoor units. Tranquility indoor Cased Coils are specifically designed and matched for use with Tranquility indoor and outdoor geothermal split units.

Tranquility Cased Coils are available in vertical upflow or downflow, and horizontal left or horizontal right airflow. Designed for retrofit geothermal installations, the ClimateMaster indoor Cased Coil is ideal for dual fuel geothermal add-on applications.



Features

- 1 Fully convertible vertical upflow or downflow, and horizontal left or horizontal right airflow
- 2 Thermoset plastic drain pan
- 3 Large easily removable access panel provides an open service-friendly cabinet
- 4 Heavy gauge galvanized steel construction with attractive grey powder coat finish

Application Flexibility

- Four Capacities: 026, 038, 049, 064
- AHRI matched and rated with TTP and TTS products
- EarthPure® HFC-410A refrigerant
- Easily connects to new or existing fossil fuel furnaces
- Large low RPM blowers with variable speed fan motors provide quiet, efficient air movement with high static capability
- Exceeds federal requirements for 30% tax credit on installation costs*
- Exceeds ASHRAE 90.1 and Energy Star 3.0 efficiencies*
- Standard 10-year limited warranty on all parts with 5-year labor allowance; Optional extended 5-year limited labor allowance available for a total of 10-year labor allowance

*When matched with ClimateMaster Tranquility Split compressor section

CLIMATEMASTER® GEOTHERMAL HEAT PUMP SYSTEMS

SMART | RESPONSIBLE | COMFORTABLE

Tranquility Cased Coil (TAC)

Performance and Specifications

Tranquility TTS/P with Tranquility Cased Coils ISO Ratings

AHRI/ISO/ASHRAE 13256-1 Data (English (IP) Units)

Model	Capacity	Water Loop Heat Pump				Ground Water Heat Pump				Ground Loop Heat Pump			
		Cooling 86°F		Heating 68°F		Cooling 59°F		Heating 50°F		Cooling Full Load 77°F Part Load 68°F		Heating Full Load 32°F Part Load 41°F	
	Modulation	Capacity Btuh	EER Btuh/W	Capacity Btuh	COP	Capacity Btuh	EER Btuh/W	Capacity Btuh	COP	Capacity Btuh	EER Btuh/W	Capacity Btuh	COP
TTS/P026	Full	25,500	14.90	29,300	5.10	28,900	22.50	25,400	4.70	26,700	17.30	20,300	4.00
	Part	19,400	17.60	22,300	6.40	22,100	29.30	18,800	5.30	21,200	24.90	16,800	4.70
TTS/P038	Full	37,400	15.40	42,400	5.10	42,000	22.60	35,500	4.70	39,100	17.60	28,300	4.10
	Part	27,600	18.30	30,700	6.20	30,500	30.10	25,300	5.20	29,800	25.80	22,500	4.60
TTS/P049	Full	49,200	15.40	55,300	5.10	54,900	22.20	46,300	4.70	50,300	17.20	35,800	4.00
	Part	37,200	17.50	42,900	6.10	42,700	28.50	34,400	5.10	39,800	23.60	30,100	4.50
TTS/P064	Full	57,100	13.70	68,700	4.60	62,400	19.90	56,200	4.10	60,100	16.00	45,300	3.60
	Part	44,400	15.70	51,900	5.30	50,600	25.60	42,400	4.50	49,000	22.10	37,900	4.00

Cooling capacities based upon 80.6°F DB, 66.2°F WB entering air temperature

Heating capacities based upon 68°F DB, 59°F WB entering air temperature

All TT ratings based upon 208V operation

Dimensional Data

Capacity - Size		Case		
		Width	Depth	Height
TAC026 - 27	in	17.5	17.9	20.0
	cm	44.4	45.5	50.8
TAC026 - 21	in	21.5	17.5	20.0
	cm	54.6	44.4	50.8
TAC038 - 21	in	21.0	17.5	20.0
	cm	53.3	44.4	50.8
TAC038 - 24	in	24.5	30.3	32.0
	cm	62.2	77.0	81.3
TAC049 - 21	in	21.0	25.9	28.0
	cm	53.3	65.8	71.1
TAC049 - 24	in	24.5	30.3	32.0
	cm	62.2	77.0	81.3
TAC064 - 24	in	24.5	30.3	32.0
	cm	62.2	77.0	81.3

Options

	Standard	Factory Option	Dealer Option
EarthPure® HFC-410A Refrigerant	●		
Thermal Expansion Valve	●		
4-Way Convertible	●		
Powder Coat Paint	●		
Extended Labor Allowance and Service Warranty		●	
Digital Multi-Stage Thermostat			●
Digital Programmable Thermostat			●
10-Year Limited Warranty	●		



7300 S.W. 44th Street
Oklahoma City, OK 73179

Phone: 405-745-6000

Fax: 405-745-6058

climatemaster.com | cmdealernet.com

ClimateMaster works continually to improve its products. As a result, the design and specifications of each product at the time for order may be changed without notice and may not be as described herein. For specific information on the current design and specifications go to cmdealernet.com. Statements and other information contained herein are not express warranties and do not form the basis of any bargain between the parties, but are merely ClimateMaster's opinion or commendation of its products.

ClimateMaster is a company of LSB Industries, Inc. New York Stock Exchange Symbol: LXU

The management system governing the manufacture of ClimateMaster's products is ISO 9001:2000 certified.



Intertek

